



HAL
open science

Growth of vertically aligned carbon nanotubes on aluminium substrate through a one-step thermal CVD process

F. Nassoy, M. Pinault, J. Descarpentries, H. Hauf, P-E. Coulon, C. Reynaud,
M. Mayne-L'Hermitte

► **To cite this version:**

F. Nassoy, M. Pinault, J. Descarpentries, H. Hauf, P-E. Coulon, et al.. Growth of vertically aligned carbon nanotubes on aluminium substrate through a one-step thermal CVD process. Carbon 2019, Jul 2019, Lexington, United States. cea-02329023

HAL Id: cea-02329023

<https://cea.hal.science/cea-02329023>

Submitted on 23 Oct 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Growth of vertically aligned carbon nanotubes on aluminium substrate through a one-step thermal CVD process

F. Nassoy^{1,2}, M. Pinault¹, J. Descarpentries², H. Hauf², P-E. Coulon³, C. Reynaud¹, M. Mayne-L'Hermite¹

¹ NIMBE, CEA, CNRS, Université Paris-Saclay, CEA Saclay 91191 Gif-sur-Yvette France;

² NawaTechnologies, Chez STMicroelectronics, 190 avenue Célestin Coq-ZI, 13106 Rousset Cedex, France;

³ Laboratoire des Solides Irradiés, CNRS, CEA-DRF-IRAMIS, Ecole polytechnique, Université Paris-Saclay, 91128 Palaiseau Cedex, France;

The aim is to grow vertically aligned carbon nanotubes (VACNT) on aluminium by a single-step process, namely the thermal aerosol assisted CCVD, in order to get a scalable process to fabricate ultracapacitor electrodes. The one-step synthesis of VACNT on such substrates requires a significant reduction in the growth temperature as compared to conventional substrates [1-3]. According to previous work, our process is based on the adjunction of hydrogen in the gas phase to promote the decomposition of the catalyst precursor at low temperature [2], and of acetylene, easy to decompose at low temperature [4]. Our approach is first to identify the most relevant synthesis parameters to reach VACNT growth on aluminium substrates by subsequently analysing the product features. This optimization study enabled to obtain clean, long and dense VACNTs at 580°C or 620°C with a growth rate (ca. 5µm/min) at the best level of the state of the art. Attention is paid on the study of VACNT thickness variation versus synthesis duration showing a limitation of CNT length from a certain time of synthesis. In order to understand this phenomenon, the trend in CNT length is examined according to different models reported in the literature, which gives evidence of a catalyst deactivation phenomenon occurring during the one step-CVD process performed at low temperature due to the additional formation of disordered carbon. In addition, the CNT/Al interface was analysed, enabling to clearly identify catalytic particles located at the CNT base and on the surface of a well-defined oxide interface layer suggesting the availability of catalyst nanoparticles for VACNT growth.

[1] M. Pinault et al, *Nano Lett.*, 2005, **5**, 2394

[2] C. Castro et al, *Carbon*, 2013, **61**, 585

[3] M. Delmas et al, *Nanotechnology*, 2012, **23**

[4] M. R. Arcila-Velez et al, *Nano Energy*, 2014, **8**, 9–16