

## **Bias identification and estimation based on data reconciliation and first-principle model application to nuclear fuel recycling process.**

A. Duterme, M. Montuir, B. Dinh, J. Bisson, N. Vigier, P. Floquet, X. Joulia

► **To cite this version:**

A. Duterme, M. Montuir, B. Dinh, J. Bisson, N. Vigier, et al.. Bias identification and estimation based on data reconciliation and first-principle model application to nuclear fuel recycling process.. ESCAPE 2019 - European Symposium on Computer Aided Process Engineering, Jun 2019, Eindhoven, Netherlands. cea-02338719

**HAL Id: cea-02338719**

**<https://hal-cea.archives-ouvertes.fr/cea-02338719>**

Submitted on 24 Feb 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# **Bias identification and estimation based on data reconciliation and first-principle model – application to nuclear fuel recycling process.**

**A. Duterme<sup>a</sup>, M. Montuir<sup>a</sup>, B. Dinh<sup>a</sup>, J. Bisson<sup>b</sup>, N. Vigier<sup>c</sup>, P. Floquet<sup>d</sup>, X. Joulia<sup>d</sup>**

**a. CEA Marcoule, Nuclear Energy Division, Research Department on Processes for Mining and Fuel Recycling, 30207 Bagnols-sur-Cèze, France**

**b. Orano La Hague Plant, Technical Department, 50444 Beaumont-Hague, France**

**c. Orano Projet, La Défense, Technical Department – R&D, 92400 Courbevoie, France**

**d. Laboratoire de Génie Chimique, Université de Toulouse, CNRS, INPT, UPS, Toulouse, France**

At La Hague plant, the PUREX process [1] recycles spent nuclear fuel. Uranium and plutonium are recovered and purified by solvent extraction. The PAREX code [2] simulates the partitioning of the species, the transfer and chemical kinetics. Industrially, high consideration is given to a specific set of hard sensors on main fluxes needed for operation, control and safety issues (multiple sensors, regular checking). A project has been launched in order to automatically estimate the process state thanks to data reconciliation and the knowledge-based simulator PAREX. The first step is to make use of secondary sensors. However, these additional data can have biases that cannot be detected with prior data. This paper offers a methodology to identify and estimate significant and numerous biases within connected fluxes.

Plant data inventory and analysis (position and type of hard sensors...) allow to determine process observability and redundancy with graph theory. First, gross error detection and identification are carried out for mass balance with linear data reconciliation (LDR): Iterative Measurement Test (IMT), Simple Serial Compensation Strategy (SSCS) and Modified Serial Compensation Strategy (MSCS) are used. Biases were only detected on secondary hard sensors in different operation conditions. This is consistent with process knowledge. However biases are not correctly shared among the inconsistent data as no test was able to detect all biased fluxes. Their performances are limited in disrupted cases: the study simultaneously displays multiple flows between two units, numerous gross errors and significant ratio between gross error and measurement variance [3].

As no main flux, hence no inflow, is biased, PAREX simulations can be used for identifying all secondary sensor bias locations. With the redundancy analysis, an offline step establishes a map of the process consistent with expert knowledge, to identify reconcilable data. Then, bias value estimation employs an online iterative approach based on PAREX and nonlinear data reconciliation (NLDR). NLDR is based on a reduced model, taking into account observable variables. PAREX code is needed to provide all flux characteristics (temperature, composition...) including bias estimation for the next NLDR. Once PAREX and NLDR bias and data estimations converge, iterations stop. This methodology reconciles data thanks to NLDR with a reduced model as known constraints and PAREX code as non-explicit constraints.

Data reconciliation and simulation are combined to locate and estimate multiple biases and to make data consistent in the case of disrupted hard sensors measuring connected flows.

## **References:**

[1] B. Dinh, P. Baron and J. Duhamet, Treatment and recycling of spent nuclear fuel, DEN Monographs, pp 55 - 70, CEA Saclay et Groupe Moniteur, Paris, 2008.

[2] J. Bisson, B. Dinh, P. Huron and C. Huel, Procedia Chemistry, Vol. 32, 2016, pp 117-124.

[3] E. Cordeiro do Valle, R. de Araújo Kalid, A. Resende Secchi, A. Kiperstok, Computers and Chemical Engineering, Vol. 111, 2018, pp 134-148.