



**HAL**  
open science

## VACNT based nanocomposite electrodes on Aluminium for innovative supercapacitors

Fabien Nassoy, Baptiste Pibaleau, Émeline Charon, François Tran-Van, Fouad Ghamouss, Pierre-Henri Aubert, Philippe Banet, Jérémie Descarpentries, Cécile Reynaud, Martine Mayne, et al.

### ► To cite this version:

Fabien Nassoy, Baptiste Pibaleau, Émeline Charon, François Tran-Van, Fouad Ghamouss, et al.. VACNT based nanocomposite electrodes on Aluminium for innovative supercapacitors. Nano2018, Jun 2018, Hong Kong, China. cea-02339982

**HAL Id: cea-02339982**

**<https://hal-cea.archives-ouvertes.fr/cea-02339982>**

Submitted on 30 Oct 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# VACNT based nanocomposite electrodes on Aluminium for innovative supercapacitors

Fabien NASSOY<sup>1,4</sup>, Baptiste PIBALEAU<sup>1,2</sup>, Emeline CHARON<sup>1</sup>, François TRAN-VAN<sup>2</sup>, Fouad GHAMOUSS<sup>2</sup>, Pierre-Henri AUBERT<sup>3</sup>, Philippe BANET<sup>3</sup>, Jérémie DESCARPENTRIES<sup>4</sup>, Cécile REYNAUD<sup>1</sup>, Martine MAYNE<sup>1</sup>, Mathieu PINAULT<sup>1</sup>

1. NIMBE, CEA, CNRS, Université Paris-Saclay, CEA Saclay 91191 Gif-sur-Yvette France, email: [martine.mayne@cea.fr](mailto:martine.mayne@cea.fr), [cecile.reynaud@cea.fr](mailto:cecile.reynaud@cea.fr); [mathieu.pinault@cea.fr](mailto:mathieu.pinault@cea.fr)
2. PCM2E, Université François Rabelais, Parc de Grandmont, 37200 Tours, France, email: [fouad.ghamouss@univ-tours.fr](mailto:fouad.ghamouss@univ-tours.fr); [francois.tran@univ-tours.fr](mailto:francois.tran@univ-tours.fr)
3. LPPI, Université de Cergy-Pontoise, site de Neuville, 95031 Cergy-Pontoise Cedex, France, email : [philippe.banet@u-cergy.fr](mailto:philippe.banet@u-cergy.fr); [aubert@u-cergy.fr](mailto:aubert@u-cergy.fr)
4. NawaTechnologies, Chez STMicroelectronics, 13106 Rousset Cedex, France, email : [jeremie.descarpentries@nawatechnologies.com](mailto:jeremie.descarpentries@nawatechnologies.com)

**Key Words:** aligned carbon nanotubes, conducting polymers, metal oxides, supercapacitors, Energy

The aim of this work is to develop innovative electrodes materials with high specific capacitance based on vertically aligned carbon nanotubes (VACNT) to be included in supercapacitors. Catalytic chemical vapor deposition (CCVD) is the best method to grow VACNT but considering the aluminium melting temperature (c.a. 660°C), the synthesis of VACNT on such substrates requires a significant reduction in the growth temperature as compared to conventional substrates [1-2]. Our approach is first to identify the most relevant synthesis parameters to achieve VACNT growth at such a low temperature by using precursor mixtures more favourable for a decomposition at low temperature [3]. Our results show that, with a single-step aerosol assisted CCVD process; it is possible to obtain clean, long and dense VACNTs on Al current collectors, with a growth rate at the best level of the state of the art at such low temperature. VACNT are then used to develop new pseudocapacitive electrode materials based on VACNT modified with Electronic Conducting Polymers (ECP) and/or metal oxide electrodeposited in a controlled manner [4]. Nanocomposite electrodes of poly-3-methylthiophene (P3MT) in ionic liquid and manganese oxide in aqueous media both homogeneously deposited on VACNT have been elaborated and evaluation of storage properties will be presented. Finally, we select best nanocomposite configurations for their upscaling in prototype modules demonstrating the industrial feasibility of the approach.

## Reference:

- [1] C. Castro et al, Carbon, 2013, 61, 585.
- [2] M. Delmas et al, Nanotechnology, 2012, 23
- [3] M. R. Arcila-Velez et al, Nano Energy, 2014, 8, 9–16
- [4] S. Lagoutte, et al., Electrochimica Acta 130 (2014) 754-765.

