

# Fabrication and characterization of evaporated hybrid perovskite based solar cells

Chloé Dindault, Bernard Geffroy, Yvan Bonnassieux, Denis Tondelier

► **To cite this version:**

Chloé Dindault, Bernard Geffroy, Yvan Bonnassieux, Denis Tondelier. Fabrication and characterization of evaporated hybrid perovskite based solar cells. Journées Perovskites hybrides (JPH2017), May 2017, Angers, France. cea-02341497

**HAL Id: cea-02341497**

**<https://hal-cea.archives-ouvertes.fr/cea-02341497>**

Submitted on 31 Oct 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Poster

## Fabrication and characterization of evaporated hybrid perovskite based solar cells

Chloé DINDAULT<sup>a,b</sup>, Bernard GEFFROY<sup>b,c</sup>, Yvan BONNASSIEUX<sup>b</sup> & Denis TONDELIER<sup>b</sup>

<sup>a</sup> Institut Photovoltaïque d'Île de France (IPVF) - 92160 Antony

<sup>b</sup> LPICM, Ecole Polytechnique, CNRS, Université Paris-Saclay - 91128 Palaiseau

<sup>c</sup> LICSEN, NIMBE, CEA, CNRS, Université Paris-Saclay, CEA Saclay - 91191 Gif Sur Yvette  
chloe.dindault@ipvf.fr

Over the last years, interest for hybrid perovskite materials as light absorber in photovoltaic devices has increased continuously, from only 14 publications in 2012 to over 2200 in 2016<sup>[1]</sup>. Hybrid perovskite deposition techniques can be sort out in two families: wet processing and vacuum deposition. If the first is the most widely used, the second appears more suitable for future commercialization of perovskite solar cells. Indeed, wet processing is highly user dependant and hardly allows homogeneous large surface deposition when vacuum based deposition permits high reproducibility between batches and homogeneity over large area.

In this context we report here experimental details to fabricate evaporated hybrid perovskite films including material densities, heating temperatures and deposition rates. The obtained layers will be characterized by absorption spectra, XRD (X-Ray Diffraction) or SEM (Scanning Electron Microscopy). Evaporated hybrid perovskite layers will also be incorporated in photovoltaic devices (structure being ITO/PEDOT:PSS/Perovskite/PCBM/Ag) and characterized by J-V and EQE (External Quantum Efficiency) measurements.



Figure a. Evaporator equipment in N<sub>2</sub>-filled glove box




Figure b. Evolution of heating temperatures and deposition rate during process: settings (blue part), during coevaporation (white part) and checking rates after coevaporation (green part)




Figure c. Absorption spectra of MAPbI<sub>3</sub> by wet processing and coevaporation




Figure d. J/V curve of a solar cell incorporating evaporated hybrid perovskite active layer (active area of 0.28 cm<sup>2</sup>)

[1] From data analysis on Web of Science for "perovskite solar cells" research (on 09.03.17)