

Electrode/electrolyte interphase evolution for next generation Li-ion batteries anodes

Antoine Desrues, John P. Alper, Florent Boismain, Cédric Haon, Sylvain Franger, Nathalie Herlin-Boime

► **To cite this version:**

Antoine Desrues, John P. Alper, Florent Boismain, Cédric Haon, Sylvain Franger, et al.. Electrode/electrolyte interphase evolution for next generation Li-ion batteries anodes. C’Nano2017, Dec 2017, Lyon, France. cea-02341512

HAL Id: cea-02341512

<https://hal-cea.archives-ouvertes.fr/cea-02341512>

Submitted on 31 Oct 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L’archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d’enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Title and affiliations (must fit in this box)**Electrode/electrolyte interphase evolution for next generation Li-ion batteries anodes**

Antoine Desrues^{1,2}, John P. Alper^{1,3}, Florent Boismain¹, Cédric Haon³, Sylvain Franger²,
Nathalie Herlin-Boime¹

1. NIMBE UMR 3685, CEA, CNRS, Université Paris Saclay, CEA Saclay, F-91191 Gif-sur-Yvette Cedex, France

2. ICMMO, CNRS UMR 8182, Univ. Paris-Sud, Université Paris-Saclay, Orsay, France

3. LITEN, CEA, 17 rue des Martyrs, F-38054 Grenoble, France

Abstract (No longer than 250 words. Both the abstract and references must fit in this box. Style is Calibri 12, single line spacing)

Performant electrochemical storage devices appear as one of the solution to face the challenge of energy transition. In this context, lithium-ion batteries are a well-developed technology¹.

This work is focused on increasing the negative electrode's capacity by understanding the degradation mechanism occurring in the material. Graphitic carbon is commonly used as a negative electrode in commercial battery systems because of its stability, electronic conductivity, and its natural abundance. However, its maximum energy density remains too low to meet the requirements of demanding applications such as electric vehicles. Silicon is a promising alternative anode material to increase its capacity up to 3579 mAh/g, ten times higher than the 350 mAh/g of graphite².

However, fractures issues occur in the material, due the high volumetric change over cycling. Using nanoparticles has been shown to alleviate the problem³ but at this size, the formation of an interphase between the electrolyte and the solid (named SEI) becomes predominant. This SEI stability is fundamental to obtain stable performance of silicon electrodes. The coating of the silicon surface by carbon has proved to protect the bare silicon surface and obtain a more stable SEI⁴.

The integration of such nanoparticles in Li-ion anodes improves the electrodes' specific capacities. Those particles are synthetized by laser pyrolysis, a one step process. Impedance spectroscopy, a powerful and non-destructive technique, is used to probe the electrode's interfaces. In this paper, using this technique, an improved stability of carbon coated silicon particles will be demonstrated by comparison to pure silicon.

1. Armand, M.; Tarascon, J.-M., *Nature* **2008**, *451* (7179), 652-657.

2. Obrovac, M.; Chevrier, V., *Chemical reviews* **2014**, *114* (23), 11444-11502.

3. Liu, X. H.; Zhong, L.; Huang, S.; Mao, S. X.; Zhu, T.; Huang, J. Y., *Acs Nano* **2012**, *6* (2), 1522-1531.

4. Terranova, M. L.; Orlanducci, S.; Tamburri, E.; Guglielmotti, V.; Rossi, M., *Journal of Power Sources* **2014**, *246*, 167-177.