

# Dimensional measurement of TiO<sub>2</sub> particles in powder form by SAXS and SEM

N Bouzakher-Ghomrasni, C. Chivas-Joly, F. Testard, O. Taché

► **To cite this version:**

N Bouzakher-Ghomrasni, C. Chivas-Joly, F. Testard, O. Taché. Dimensional measurement of TiO<sub>2</sub> particles in powder form by SAXS and SEM. SFNano - C'Nano, Dec 2019, Dijon, France. 10.3762/bj-nano.6.181 . cea-02403840

**HAL Id: cea-02403840**

**<https://hal-cea.archives-ouvertes.fr/cea-02403840>**

Submitted on 11 Dec 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

**Thematic Session:** POSTER Nanomaterials

**Keywords:** Size, TiO<sub>2</sub>, SAXS, SEM, Nanomaterials

## Dimensional measurement of TiO<sub>2</sub> particles in powder form by SAXS and SEM

**N. Bouzakher-Ghomrasni<sup>a,b</sup>, C. Chivas-Joly<sup>a</sup>, F. Testard<sup>b</sup>, O. Taché<sup>b</sup>**

<sup>a</sup> Laboratoire National de métrologie et d'Essais – 29 avenue Hennequin, 78197 Trappes Cedex (France)

<sup>b</sup> LIONS, NIMBE, CEA, CNRS, Université Paris Saclay, CEA Saclay, 91191 Gif-sur-Yvette, France

Developments of nanomaterials had an important known evolution during the last thirty years for different industrial sectors<sup>1</sup>. Titanium dioxide is one of the most produced and exploited nanomaterials in the industry<sup>2</sup>. Indeed, TiO<sub>2</sub> has various applications; it can be used as a white pigment for paint and food products and is also used as a UV filter in sunscreen lotions. The characterization of TiO<sub>2</sub> nanoparticles, contained in consumer products remains a challenge because of their structure (polydispersity, polymorphism) and their environment which remains generally complex and requires several characterizations techniques. Electron microscopies are the first recommended techniques for the dimensional characterization of nanomaterials. In comparison with the results obtained by the scanning electron microscope (SEM), another technique, SAXS (Small Angle X-Ray Scattering), can be used for the indirect characterization of nanomaterials (simple or introduced into a complex matrix).

The first step of this study is to compare the dimensional measurements of TiO<sub>2</sub> nanoparticles in powder form with two different techniques: SEM (direct method) and SAXS (indirect method) and with two different measurands, an equivalent area diameter for SEM and specific surface area for SAXS. The second part should be to avoid the sampling preparation steps with *in situ* dimensional measurement.

<sup>1</sup> Van Broekhuizen F.A. and van Broekhuizen J.C., Nanotechnology in the European Construction Industry, State of the art, Executive Summary. European Commission, 2009

<sup>2</sup> Marina E. Vance, Todd Kuiken, Eric P. Vejerano, Sean P. McGinnis, Michael F. Hochella Jr., David Rejeski and Matthew S. Hull, Nanotechnology in the real world: Redeveloping the nanomaterial consumer products inventory, Beilstein J. Nanotechnol. 2015, 6, 1769–1780. doi:10.3762/bjnano.6.181.