

SOL modelling of the JT-60SA tokamak initial operational scenario using SOLEDGE-EIRENE code

K Galązka, L Balbinot, G L Falchetto, N Rivals, P Tamain, Y Marandet, H Bufferand, P Innocente, G Ciraolo

▶ **To cite this version:**

K Galązka, L Balbinot, G L Falchetto, N Rivals, P Tamain, et al.. SOL modelling of the JT-60SA tokamak initial operational scenario using SOLEDGE-EIRENE code. 48th EPS conference on plasma physics, Jun 2022, videoconference, Netherlands. cea-03766515

HAL Id: cea-03766515
https://cea.hal.science/cea-03766515

Submitted on 1 Sep 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

SOL modelling of the JT-60SA tokamak initial operational scenario using SOLEDGE-EIRENE code

K. Gałązka[1, 2], L. Balbinot[3], G. L. Falchetto[1], N. Rivals[1], P. Tamain[1], Y. Marandet[4], H. Bufferand[1], P. Innocente[3] and G. Ciraolo[1]

1 CEA, IRFM, F-13108 Saint-Paul-Lez-Durance, France

2 IFPiLM, ul. Hery 23, 01-497 Warszawa, Poland

3 Consorzio RFX, Corso Stati Uniti 4, 35127 Padova, Italy

4 Aix-Marseille Univ., CNRS, PIIM, Marseille, France

Introduction&Background

The main aim of this work is to assess the realistic heat loads on the first wall of the JT-60SA tokamak. To achieve this scope, for the first time the entire chamber and the subdivertor region is modeled by the fluid transport code SOLEDGE3X-EIRENE [1]. Whereas the full power scenario #2 modeling was reported elsewhere [2] here we focus on scenario #2 initial phase with carbon divertor and limited heating power P_{aux}, which is the main scanned parameter. Standard computational mesh with pumps situated next to the strike points (STD) is compared with full chamber + subdivertor mesh (SUBD).

Scenario #2 main parameters [3]:

$\langle n_e \rangle = 5.6\times10^{19}$ m^{-3}

$P_{aux}^{max} = 19/26.5/33$ MW

$n_e^{sep} < 2.5\times10^{19}$ m^{-3}

References:


[1] H. Bufferand et al 2021 Nucl. Fusion 61 116052 (2021)

[2] N. Hayashi, et al., Proc. 26th IAEA Fusion Energy Conf., (2016)


[3] JT-60SA Research Plan, Ver. 4, 2018/09

[4] L. Balbinot et al., in preparation

Simulations setup



Standard configuration (**STD**)



Subdivertor configuration (**SUBD**)

Input power @ core boundary scan:

P_{aux} = [15, 17.5, 20, 22.5, 25, 27.5, 30] MW

Particle source @ core: $S_i = 1\times10^{21}$ part./s

Deuterium fuelling: $\Gamma_D = 1\times10^{21}$ part./s

C sputtering - Bohdansky formula

EIRENE with simplified Kotov model (no elastic collisions on neutrals)

No drifts

Wall properties:

$R_D = 1.0$

$R_C = 0.1$


Pump albedo:

$R_D = 0.95$


$R_C = 0.1$

OMP profiles

Transport coefficients@OMP [4]




n_e, T_e comparison for P_{aux} = 15 MW



Power scan - pure D plasma


OMP profiles




H-mode		P_{aux}
STD	SUBD	[MW]
		15
		17.5
		20
		22.5
		25
		27.5
		30

- Rise of n_e with increasing P_{aux} (stronger for pure-D cases)
- Imited effect on T_e profile
- rise of n_C with increasing P_{aux}
- negligible effect of different geometry


Target profiles - electron density & temperature




Target profiles - heat load




Q_0 - heat load by neutrals






Neutrals pressure 2D map




STD geometry




- large pressure difference between the inner and the outer divertor volume

Power scan - D+C plasma

OMP profiles




C radiation power




- most C radiation in the outer divertor
- inner divertor 2x less effective in term of power dissipation
- P_{RAD}^{C}[OUTER DIV] visibly lower for the SUBD geometry
- larger PFR radiation for the SUBD geometry


Target profiles - electron density & temperature




Target profiles - heat load




Q_0 - heat load by neutrals






Neutrals pressure 2D map



SUBD geometry



- subdivertor presence results in more equal neutrals distribution in inner and outer divertor

Conclusions

- a power scan was performed for the JT-60SA initial research phase fully inductive scneario #2 of JT-60SA in the range of [15, 30] MW
- increase in P_{aux} leads to increase of n_e^{sep}, which for pure-D cases exceeds the nominal n_e in the core, 5.6×10^{19} m^{-3}, already for P_{aux}=20 MW
- in D+C cases the nesep rise is less pronounced, a rise in n_C is observed from 1.6×10^{18} m^{-3} for P_{aux}=15 MW to $n_C=4.0\times10^{18}$ m^{-3} for P_{aux}=30 MW
- dominant C radiation losses take place in the divertor, the role of the main chamber SOL and CORE volume is limited, D-related losses are ~ 0.7-1.0 MW for all cases
- already for the lowest P_{aux}=15 MW cases the peak heat load exceeds the 10 MW/m^2 limit; as in previous research [4], additional power dissipation mechanism is required
- the presence of subdivertor causes local differences in neutral density, but has only minor effect on the final result: 1-1.5 MW lower of P_{RAD}^{C}[TOTAL] for P_{aux}>22.5 MW

This work has been carried out within the framework of the EUROfusion Consortium, funded by the European Union via the Euratom Research and Training Programme (Grant Agreement No 101052200 — EUROfusion). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Commission. Neither the European Union nor the European Commission can be held responsible for them.